	Quantity & Unit	Item Description (Completed Commodity Number or Class/Sub-Class must be furnished for each item)
Line : 00001	3 ea	Treadmill Matrix Cardio Brand T5X or equal Incline range: Minimum of 0-15% Speed range: 0.5-12mph Console display: dot matrix LED or LCD Console display feedback: time, distance, calories, speed, incline, pace, heart rate, METs, watts Workouts: manual, rolling hills, fat burn, 5k, target, HR, Gerkin protocol, Army PFT, Navy PRT, Marine PFT, Air Force PRT, physical efficiency battery (PEB) Crossbar controls: quick start, stop, and cool down Manager mode: resettable defaults with accumulated time and distance Maximum user weight: 400 lbs Minimum Warranties: Frame: 7 years Drive Motor: lifetime Parts: 3 years CAP Labor: 3 years CAP One button quick start, pause function, on the fly program change, Fit Touch Technology, wireless data transmitter, iPod compatible, personal fan Treadmill must have the capabilities to absorb impact for best possible feel, Continuously monitors and adjusts to user's foot fall, and wireless trans- mitters to allow for service providers and users to continuously monitor product performance.
Line: 00002	2 ea	Total Body Elliptical Features: Matrix E 3XC or equal Contact and telemetric HR sensors, cushioned footpads Handlebar design: Multi-position dual action and ergo bend stationary Thumb switch controls Console: Display type-LED or LCD Display Feedback: time, distance, calories, speed, RPM, heart rate, METs, watts,profile CSAFE, on the fly program change, Manager mode: resettable defaults with accumulated time and distance Technical Specifications:

		Maximum user weight: 400 lbs Electrical requirements: self-power, AC power option Minimum Warranties: Frame: 7 years Generator: 5 years Parts: 3 years CAP Labor: 3 years CAP Elliptical must be cordless and feature maintenance-free generators that do not require a battery to start. Foot Pad should be designed to absorb shock and reduce stress on the knees, feet and ankles.
Line:00003	1 ea	Recumbent Cycle Features: Matrix R3x or equal Contact and telemetric HR sensors: Handlebar design: seat side and front horizontal ergo bend. Thumb switch controls Minimum watts: 13 watts Minimum RPM: 20 Resistance levels: minimum of 25 Console: Display LED or LCD Display feedback: Time, distance, speed, calories, RPM, level, heart, rate, watts, and profile Workouts: manual, rolling, intervals, fat burn, random, fit test, target HR, constant watts CSAFE, Professional Certified, on the fly program, Manager mode: resettable defaults with accumulated time and distance Technical specifications: Crank design: single piece Maximum user weight: 400 lbs Minimum Warranties: Frame: 7 years Generator: 5 years Parts: 3 years CAP Labor: 3 years CAP
Line: 00004	1 ea	Plate Load Supine Bench Press Matrix G3PL13, or equal converging independent arms, two integrated weight storage horns, coated grips
Line: 00005	1 ea	Round metal tubing with clear powder coat. Plate Load Incline Bench Press Matrix G3PL14, or equal converging independent arms, four integrated weight storage horns

1	ľ	five-position adjustable seat pad with gas spring assist, 45 degree incline back pad
		Round metal tubing with clear powder coat.
ine: 00006	1 ea	Plate Load Seated Calf Press
Ellio, doddd	100000000	Matrix G3PL77, or equal
		seat will move with input arm for maintenance of alignment
		knee pads adjust for tibia length and range of motion
		quick-release bar catch
		Round metal tubing with clear powder coat.
Line: 00007	1 ea	Selectorized Abdominal Crunch
		Matrix G3S51, or equal
		dual axis of rotation to produce a natural crunch movement that maximizes abdominal contraction.
		seat and handle position designed for stability
		Round metal tubing with clear powder coat.
ine: 00008	1 ea	Selectorized Combination Pieces: Biangular transformer
		Magnum E Series MBT200 or equal
		Constructed of 11 guage steel tubing
		Materials must be highly resilient and shaterproof
		A full motion machine that allows the user to work three different body parts with
		six (6) different multiplane movement patterns: incline press, lat roll, benchpress, shoulder press,
		Hi row, and lat pulldown.
		Stack weight: minimum of 312 lbs
_ine: 00009	1 ea	Varsity Adjustable Decline Bench/Sit Up
	l	Magnum D61or equal
		split angled pad design with padded leg rollers to lock user in proper position for decline
	1	exercises and abdominal work.
		Constructed of 11 guage steel tubing
_ine: 00010	1 ea	Varsity Adjustable Crunch Board
		Magnum D77 or equal
		split pad design and double adjustable roller pads to lock any size user in proper position
	l	handle mounted on front rollers
		Constructed of 11 guage steel tubing
_ine: 00011	1 ea	Varsity Dip/Leg Raise w/Chin
	l	Magnum D63C or equal
		compact design to allow user to perform dips, chin ups, and leg raises all from the
		same side. Covered grips.
		Constructed of 11 guage steel tubing
_ine:00012	1 ea	Plate Load Perfect Squat
		Magnum 400 or equal
		large angled diamond plate foot platform
		adjustable starting point to allow user to set pad height for squats or standing calf raises
		shoulder pads must maintain parallel position to floor throughout full range of motion
		two weight storage pegs

1 ea	Biangular Plate Load Lat Row
	Magnum 420 or equal
	biangular mechanism to create a controlled natural, diverging, rear motion exercise pattern
	lever lock seat height adjustment, adjustable chest pads. Padded seat.
	Constructed of 11 guage steel tubing
1 ea	Free Standing Leg Extension
	Magnum FS901 or equal
	Weight Stack minimum of 265 lbs. Padded seat and leg rollers.
	Constructed of 11 guage steel tubing
1 ea	Free Standing Leg Curl
	Magnum FS902 or equal
	Frame must feauture a minimum of 11 guage, 2"x3" and 3"x3" steel tubing. All feet will have rubber
	floor contacts. Frames must be welded with a lifetime warranty. All component parts should be
	fixture welded. Finish should be scratch resistans, durable, electrostatic powdercoat paint. Pieces
	should include scratch guard.
	Must provide a minimum of 3 upholstery colors and uphostery must be stain and abrasion
	resistant.
	Hook plates: should be steel adjustment plates and must utilize a safety slot design. Bar stops
	should be adjustable in 3" increments.
	Weight Storage: Must have self-contained weight storage unit with racks. Pags should be steel with
	plastic tubing covers for scratch resistance.
	4200 lb minimum tensile strength aircraft quality cable. Fiberglass impregnated nylon pulleys
	with sealed ball bearings. Unit must ionclude steel plated guide rods for multi-function bench.
	Should be ground case hardened shafting for leg press machines. Bearings should be UHMW
	polyethelene bushing blocks.
	Minimum Warranties:
	Frames - Lifetime
	Bearings Bushings - 5 years
	Cables - 1 year
	Upholstry - 90 days for wearthrough and stitching
	Parts (specified) - 1 year
2 02	STS Half Rack-Silver
2 0a	York STS 55009 (silver)or Equal
	including weight storage pegs (45, 35, 25, 10, 5, and 2.5 lbs plates)
	The Half Rack accommodates all available option. Includes: the combo grip pull-up bar,
	Min.90" high, solid cold rolled steel bar with v-shaped in the
	center, 1- pair single bar holder, 1 bench stringer
	Stainless steel hook-plates-Adjustable to at least 19 positions on min 3" center increments
	Two welded vertical bar holders
	(0.000000000000000000000000000000000000

Line: 00017	2 ea	Multi-function bench with wheels-silver York STS 55004 (silver)or equal Back Pad and seat pad Adjustable bench, spotting platforms Designed to lock into modular rack and equally functional as a stand-alone dumbell bench bench back/seat adjustments provide for a minimum of, 30, 40, 65, and 90 degrees of inclination Minimum of 6-position depth adjustor to allow bench to slide forward or backward of bushing blocks on a steel guide rod. Must be unnecessary to disengage the bench from the rack to allow user to adjust for individual torso length. Lock feature to allow the bench to lock into the rear stringer of the modular racks diamond-plate spotting platforms Two impact-resistant rubber wheels with self lubricating bearings and foam grip handles.
Line: 00018	2 ea	Flat to incline bench-silver York STS 55027 (silver) or equal Adjustable to six positions allow for a variety of dumbbell exercises handle and wheels on metal base for easy movement high-density foam padding.
Line: 00019	1 ea	Preacher Curl Bench-Silver York STS 55031or Equal Adjustable seat pad polished chrome bar holders heavy contour foam padding metal base
Line: 00020	1 ea	35 Degree Leg press York STS 55035 or Equal extra-wide footplate heavy-duty linear bearings seat-back adjustable, padded built-in weight storage Minimum 1200 pound capacity adjustable safety stops, metal base
Line: 00021	1 ea	Free Standing Cable Crossover York STS silver equipment should polished chrome with adjustable cable column, pulley swivel, pronated grip position chin-up bar. minimum 4200 lb tensile strength aircraft quality cable 2 ea - minimum 200 lb weight stacks standard

Line: 00022	1 ea	Low Row-Silver York STS Low Row-Silver The components must allow users to perform various exercises at one station step-through design for easy access. Large diamond-plated footplate Rubber covered machine attachment rest Minimum 225 lbs weight stack minimum 4200 lb tensile strength aircraft quality cable
Line: 00023	1 ea	Lat Pull down-Silver York STS or equal Adjustable locking leg hold-down Straight bar with angled ends to ensure correct arm and wrist position. minimum 4200 lb tensile strength aircraft quality cable Minimum 225 lbs weight stack
Line: 00024	1 ea	Triceps Station-Silver York STS 54048or Equal Must provide padded vertical support for the back An overhead pulley attachment system minimum 4200 lb tensile strength aircraft quality cable, Minimum 200 lbs weight stack Must be compatible with Cable Crossover bid
Line: 00025	1 ea	4-way Connector Kit-Silver York STS 55022or Equal 4 way steel connector and u-bar which allows up to 4 systems to be attached to the Cable Crossover system, on either end.
Line: 00026	1 ea	3 Tier Tray Dumbbell Rack-black York 69129 or equal Holds minimum of 15 pairs of dumbbells at least 16" deep formed steel trays Rubber strips line tray to protect dumbbells
Line: 00027	1 ea	5-80lbs Rubber Hex Dumbbell Set York 34025 or equal Dumbbell sets must have contoured knurled chrome handles and durable rubber covered heads Heads should be torque threaded and permanently affixed to a thick min. 35mm solid steel shaft. The smaller handles should graduate up from 25mm grip to 35mm grip for 20-125 lbs increments
Line: 00028	2 ea	300 lbs. Iron weight Set (2x45, 35, 25, 10, 2.5, and 4.5) 32113 York ISO-Grip International Rubber 29026 or equal Set includes one (1) 7', 300 mm, 1000 lbs Test Bar. Set should include rubber plates

		and one (1) pair of spring collars.
Line: 00029	26 ea	45 lbs Olympic Grip Plate-Black York 29025 or equal ISO-Grip Rubber Encased Steel Composite
Line: 00030	16 ea	25 lbs Olympic Grip Plate-Black York 29023 or equal ISO-Grip Rubber Encased Steel Composite
Line: 00031	16 ea	10 lbs Olympic Grip Plate-Black York 29022 or equal ISO-Grip Rubber Encased Steel Composite
Line: 00032	16 ea	5 lbs York Olympic Grip Plate-Black York 29021 or equal ISO-Grip Rubber Encased Steel Composite
Line: 00033	8 ea	2.5 lbs York Olympic Grip Plate-Black York 29020 or equal ISO-Grip Rubber Encased Steel Composite
Line: 00034	1 ea	7' Hard Chrome Bar York North American 32112 or equal 1500 lb Test-32mm
Line: 00035	2 ea	Curl Bar w/Rubber Grips York International 32030 or equal Curl bars must possess min. 30mm rubber grips, chrome
Line: 00036	1 ea	Olympic Plate Tree-Black York 69139 or equal Must have a six weight storage capacity with pegs for sorting plates from 2.5 lbs through 45 lbs. storage provided on base for 2 olympic bars York or equal
Line: 00037	3 ea	2" Chrome Spring Collars(bulk) pair York 36040 or equal Collars must possess rubber handles
		The Alabama Criminal Justice Training Center is requesting delivery and setup of the fitness center equipment be made to the new training facility currently under construction, and is scheduled for completion in August of 2010. Installation and set-up charges must be included in bid pricing